

## MEDIUM SIZES SAFES - MECHANICAL COMBINATION LOCK SERIES **BOOIL FIRE RESISTANT SAFES WITH IMPACT TEST**

Ideal for homes and businesses use. These safes has bigger capacity to keep and protects all your valuables and important documents from fire and burglary attempts









### **BS-C610**

H W D (mm) 610 500 515 (Ext) 410 360 310 (Int)

93 kg 45.76 litres Shelf: 1 pce Tray: 1 pce

## **BS-C670**

52.45 litres

H W D (mm) 670 500 515 (Ext) 470 360 310 (Int) 105 kg

Shelf: 1 pce

# BS-C750

H W D (mm) 750 530 555 (Ext) 550 390 345 (Int) 140 kg 74 litres

Shelf:1 pce Lockable drawer: 1 pce Lockable drawer: 1 pce

#### BS-C880

H W D (mm) 880 590 555 (Ext) 666 446 345 (Int)

180 kg 102.48 litres Shelf: 2 pcs

Lockable drawer: 1 pce

### **FIRE-TEST AUTHORITY**

1 to 2 (TWO) hours fire-tested @1010C / 1850°F and DROP Test

**KS** Korea Standard Association (KS G 4500 / 60P) **JIS** Japanese Industrial Standards (JIS S 1037 / PR 1T)

SP Swedish National Testing + Research (SP NT - Fire 017/60P / 90P)

**GOST** Russian Industrial Standard (120 MINS)



### **FEATURES**

**KOREA** Origin

# 3-wheel Mechanical combination lock System

RESETTABLE - Users can select / reset nos. to your own choice

# Keylock (3 keys) – User can choose to lock with key / without key

Body Strong construction consisting of heavy-gauge steel shells and

Inner + Outer monolithic anti-penetration / anti-fire material which insure excellent

protection against burglary attack and fire. Overall thickness of

body: 75 to 80mm

Tongue and Grove closure design – Deep setting bolt secure firmly into Door

the frame to prevent the penetration of fire and hot gases in event of

fire

Boltwork 2 to 3-way locking bolts

(Bolts size: 25mm dia.) Extend automatically as soon as the door is in

the fully closed position.

RELOCKING DEVICES is provided on Combination lock – will

automatically activated when the Combination lock is damaged by force

2 (TWO) years against any manufacturing defects on all locking parts Warranty